

CLAIMS

What is claimed is:

- 1 1. A method for network-based configuration of a programmable logic device,
2 comprising the steps of:
3 (a) initiating a default application on a programmable logic device;
4 (b) sending a file request for configuration data from the logic device to a server
5 located remotely from the logic device utilizing a network;
6 (c) receiving the configuration data from the network server;
7 (d) utilizing the configuration data for configuring the logic device to run a second
8 application; and
9 (e) running the second application on the logic device.
- 1 2. A method as recited in claim 1, wherein the configuration data is received in the
2 form of a bitfile.
- 1 3. A method as recited in claim 1, wherein the logic device includes at least one
2 Field Programmable Gate Array (FPGA).
- 1 4. A method as recited in claim 3, wherein a first FPGA receives the configuration
2 data, wherein the first FPGA configures a second FPGA utilizing the
3 configuration data.
- 1 5. A method as recited in claim 3, wherein the logic device includes first and
2 second FPGA's that are clocked at different speeds.
- 1 6. A method as recited in claim 1, wherein the default application and the second
2 application are both able to run simultaneously on the logic device.

- 1 7. A method as recited in claim 1, wherein the logic device further includes at least
2 one of a display screen, a touch screen, an audio chip, an Ethernet device, a
3 parallel port, a serial port, a RAM bank, and a non-volatile memory.
- 1 8. A computer program product for network-based configuration of a
2 programmable logic device, comprising:
3 (a) computer code for initiating a default application on a programmable logic
4 device;
5 (b) computer code for sending a file request for configuration data from the logic
6 device to a server located remotely from the logic device utilizing a network;
7 (c) computer code for receiving the configuration data from the network server;
8 (d) computer code for utilizing the configuration data for configuring the logic
9 device to run a second application; and
10 (e) computer code for running the second application on the logic device.
- 1 9. A computer program product as recited in claim 8, wherein the configuration
2 data is received in the form of a bitfile.
- 1 10. A computer program product as recited in claim 8, wherein the logic device
2 includes at least one Field Programmable Gate Array (FPGA).
- 1 11. A computer program product as recited in claim 10, wherein a first FPGA
2 receives the configuration data, wherein the first FPGA configures a second
3 FPGA utilizing the configuration data.
- 1 12. A computer program product as recited in claim 10, wherein the logic device
2 includes first and second FPGA's that are clocked at different speeds.

1 13. A computer program product as recited in claim 8, wherein the default
2 application and the second application are both able to run simultaneously on the
3 logic device.

1 14. A computer program product as recited in claim 8, wherein the logic device
2 further includes at least one of a display screen, a touch screen, an audio chip, an
3 Ethernet device, a parallel port, a serial port, a RAM bank, and a non-volatile
4 memory.

1 15. A system for network-based configuration of a programmable logic device,
2 comprising:
3 (a) logic for initiating a default application on a programmable logic device;
4 (b) logic for sending a file request for configuration data from the logic device to a
5 server located remotely from the logic device utilizing a network;
6 (c) logic for receiving the configuration data from the network server;
7 (d) logic for utilizing the configuration data for configuring the logic device to run a
8 second application; and
9 (e) logic for running the second application on the logic device.

1 16. A system as recited in claim 15, wherein the configuration data is received in the
2 form of a bitfile.

1 17. A system as recited in claim 15, wherein the logic device includes at least one
2 Field Programmable Gate Array (FPGA).

1 18. A system as recited in claim 17, wherein a first FPGA receives the configuration
2 data, wherein the first FPGA configures a second FPGA utilizing the
3 configuration data.

- 1 19. A system as recited in claim 17, wherein the logic device includes first and
2 second FPGA's that are clocked at different speeds.
- 1 20. A system as recited in claim 15, wherein the default application and the second
2 application are both able to run simultaneously on the logic device.
- 1 21. A system as recited in claim 15, wherein the logic device further includes at
2 least one of a display screen, a touch screen, an audio chip, an Ethernet device, a
3 parallel port, a serial port, a RAM bank, and a non-volatile memory.

For the reasons